

Serial No. 10/660,183
Customer No. 24498

PF020113

RECEIVED
CENTRAL FAX CENTER

OCT 15 2007

Listing and Amendments to the Claims

1. (Currently amended) Method for connecting a device not having wireless communication capability to a wireless network; characterized, at the level of a bridge device comprising means for adapted to interface interfacing with the wireless network comprising an access point, by the steps of:

- detecting a connection between the device and the bridge device;
- determining an address for the device and for the bridge device ; and
- ~~have the bridge device separately register;~~ registering to the access point,

with the respective addresses. the device and itself as wireless devices on the wireless network, wherein the registration is performed through an authentication and an association process of the type as defined by the IEEE 802.11 standard.

2. (Original) Method according to claim 1 wherein the addresses are MAC addresses.

3. (Original) Method according to claim 1, further comprising the step of having the bridge device monitor traffic on the wireless network for the device.

4. (Original) Method according to claim 1, further comprising the step of programming packet filters for packets having as destination address the address of the device, and upon detection of such a packet, acknowledging receipt of said packet in place of the device.

Serial No. 10/660,183
Customer No. 24498

PF020113

5. (Original) Method according to claim 3, further comprising at least one of the following steps:

- forwarding all multicast packets detected on the wireless network from the bridge device to the connected device;
- forwarding all broadcast packets detected on the wireless network from the bridge device to the connected device;
- forwarding unicast packets on the wireless network having as destination address the address of the connected device to that device.

6. (Original) Method according to claim 4, further comprising at least one of the following steps:

- forwarding all multicast packets detected on the wireless network from the bridge device to the connected device;
- forwarding all broadcast packets detected on the wireless network from the bridge device to the connected device;
- forwarding unicast packets on the wireless network having as destination address the address of the connected device to that device.

7. (Original) Method according to claim 1, where the connection between the device and the bridge device is an Ethernet connection, and wherein the step of detecting the connection comprises monitoring packets on the Ethernet connection for detecting a previously unknown source address of an Ethernet device.

Serial No. 10/660,183
Customer No. 24498

PF020113

8. (Original) Method according to claim 3, where the connection between the device and the bridge device is an Ethernet connection, and wherein the step of detecting the connection comprises monitoring packets on the Ethernet connection for detecting a previously unknown source address of an Ethernet device

9. (Original) Method according to claim 5, where the connection between the device and the bridge device is an Ethernet connection, and wherein the step of detecting the connection comprises monitoring packets on the Ethernet connection for detecting a previously unknown source address of an Ethernet device

10. (Original) Method according to claim 1, wherein the wireless network is of the IEEE 802.11 type, further comprising the step of maintaining a single management information base for both the bridge device and the connected device.

11. (Original) Method according to claim 3, wherein the wireless network is of the IEEE 802.11 type, further comprising the step of maintaining a single management information base for both the bridge device and the connected device.

12. (Original) Method according to claim 4, wherein the wireless network is of the IEEE 802.11 type, further comprising the step of maintaining a single management information base for both the bridge device and the connected device.

Serial No. 10/660,183
Customer No. 24498

PF020113

13. (Original) Method according to claim 5, wherein the wireless network is of the IEEE 802.11 type, further comprising the step of maintaining a single management information base for both the bridge device and the connected device.

14. (Currently amended) Bridge device ~~adapted~~ comprising means for communication on a wireless network and for connection of a first device not having wireless communication capability to a wireless network comprising an access point, said bridge device comprising:

- means for determining an address of the first device and of the bridge device;
- means for carrying out two separate device registrations on the wireless network, one for the bridge device, and one for the first device, using respective addresses, wherein the registration is performed through an authentication and an association process of the type as defined by the IEEE 802.11 standard.

15. (New) Method for connecting a device not having wireless communication capability to a wireless network; characterized, at the level of a bridge device adapted to interface with the wireless network, by the steps of:

- detecting a connection between the device and the bridge device;
- determining an address for the device and for the bridge device; and
- separately registering as a wireless device, with the respective addresses, the device and itself to the wireless network, wherein the registration is performed through an authentication process of the type as defined by the IEEE 802.11

Serial No. 10/660,183
Customer No. 24498

PF020113

standard.

16. (New) Bridge device adapted for communication on a wireless network and for connection of a first device not having wireless communication capability, said bridge device comprising:

- means for determining an address of the first device and of the bridge device;
- means for carrying out two separate device registrations, one for the bridge device, and one for the first device, using respective addresses, wherein the registration is performed through an authentication process of the type as defined by the IEEE 802.11 standard.